

More Power in Less Fuel Consumption Low Maintenance Cost

Available Tractor Range 20 HP to 100 HP



AVENGER 20 4WD

Technical Specifications

ENGINE					
Model / Make	AVENGER 20 4	AVENGER 20 4WD			
HP Category	20	20			
Туре	4 Stroke, Liq	4 Stroke, Liquid Cooled,			
	Direct Injecti	Direct Injection			
No. of Cylinders	3	3			
Bore / Stroke (mm)	76 / 70	76 / 70			
Rated Engine (RPM)	3000	3000			
Displacement (cc)	953	953			
Fuel Pump	In-Line Type	In-Line Type (ND-PFR M TYPE)			
Air Cleaner Type	Dry Type	Dry Type			
Cooling System	Water Coole	Water Cooled			
CLUTCH	22				
Туре	Heavy Duty I	Heavy Duty Dry Type Single			
Plate Size	Dia 224 mm	Dia 224 mm			
TRANSMISSION	2				
Gear Box	6F + 2R Con	nbination of Sy	nchromesh & S	liding Mesh	
ROAD SPEED KM	l/hr FOR\	FORWARD REVERSE		RSE	
Gear	HIGH	LOW	HIGH	LOW	
1	6.31	1.60	4.74	1.20	
2	10.63	2.70			
3	17.09	4.34			
HYDRAULIC SYS	TEM				
Type	2 Lever, ADD	2 Lever, ADDC			
Hydraulic Pump	Gear Type	Gear Type			
Linkage	TPL Category	TPL Category I			
Lifting Capacity (kg)	1000	1000			
STEERING	4				
Туре	Power Steer	Power Steering			
POWER TAKE OF	F				
Splines	6	6			
DTO / Cased		540 @ 2150 Live PTO			
PTO / Speed	540 @ 2150	Live PTO			

CAPACITIES (LITRES)		
Fuel Tank	25	
Engine Sump	4.2	
Cooling System	4.8	
Transmission & Hydraulic	26	
Steering System	1.3	
ELECTRICAL INSTALLA	ATION	
Battery	12V, 65Ah	
Alternator	12V, 40A	
Starter Motor	12V, 1.2 KW	
MIN. TURNING RADIUS	3	
Without Brakes (m)	2.5	
TYRE SIZE	4WD	
Front	5.00 - 12	
Rear	8.00 - 18	
Weight (Kg.)	1150	
FRONT DRIVE AXLE for	4WD Only	
ifferential		
Total Ratio	1:11.27	
Oil Capacity (Ltr.)	2.5±10%	
BRAKES		
Туре	Multi Disc Oil Immersed	
DIMENSIONS	Ver-	
Overall Length	2923 mm	
Width	1070 mm	
Height	2325 mm	
Ground Clearance	180 mm (Min.) 250 mm (Max.)	
Wheel Base	1580 mm	
Front Track 950 mm		
Rear Track 835 mm		

For further details please contact nearest dealer

E-mail: info@avenger.co.in | Website: www.avenger.co.in