

AVENGER 20 with Agri Tyres

Technical Specifications

ENGINE						
Model / Make	MVL3E / MHI					
HP Category	20					
Туре	4 cycle, Vertical Overhead Valve, Cylinder in line,					
	Swirl Chamber type					
No. of Cylinders	3					
Bore / Stroke (mm)	76 / 70					
Rated Engine (RPM)	3000					
Displacement (cc)	953					
Fuel Pump	In-Line Type (ND-PFR M TYPE)					
Air Cleaner Type	Dry with clogging sensor					
Cooling System	Water Cooled					
CLUTCH						
Type	Heavy Duty Dry Type Single Clutch					
Plate Size	Dia 224 mm					
TRANSMISSION						
Gear Box	9F + 3R Constant Mesh					
ROAD SPEED KM/hr	F	FORWARD REVERSE			E	
Gear	HIGH	MED	LOW	HIGH	MED	LOW
1	10.28	5.19	1.63	11.89	6.00	1.89
2	14.53	7.33	2.31			
3	23.89	12.06	3.80			
HYDRAULIC SYSTEM						
Туре	Open Center, ADDC					
Hydraulic Pump	Gear Type					
Linkage	TPL Category N					
Lifting Capacity (kg)	750					
STEERING						
Type	Power Steering					
POWER TAKE OFF						
Туре	2 Speed					
Splines	6					
PTO / Speed	540 @ 2500 540 E @ 2035					

	roominaa opoomaationo			
CAPACITIES (LITRES)				
Fuel Tank	25			
Engine Sump	3.7			
Cooling System	5.8			
Transmission & Hydraulic	18±10%			
ELECTRICAL INSTALLATION				
Battery	12V, 65Ah			
Alternator	12V, 65A			
Starter Motor	12V, 1.7 KW			
MIN. TURNING RADIUS				
Without Brakes (m)	2.6			
TYRE SIZE	Agriculture Tyre			
Front	5.00 - 12			
Rear	8.00 - 18			
Weight (Kg.)	1130			
FRONT DRIVE AXLE for 4WD Only				
Differential				
Total Ratio	1:13.81			
Oil Capacity (Ltr.)	3.2 Ltr.			
BRAKES				
Туре	Multi Disc Oil Immersed			
DIMENSIONS	Agriculture Tyre			
Overall Length	2860			
Width	1120			
Height	2570			
Ground Clearance	293			
Wheel Base	1542			
Front Track	860			
Rear Track	820			

For further details please contact nearest dealer

AVENGER TRACTORS

Patiala Road, Nabha-147 201 (Pb.) INDIA

E-mail: info@avenger.co.in | Website: www.avenger.co.in