



EUROPEAN SERIES

**Definitely Built for  
Hardcore Performance**

**AVENGER 26 4WD**



**More Power in Less Fuel Consumption  
Low Maintenance Cost**

Available Tractor Range  
20 HP to 100 HP



# AVENGER 26 4WD

## Technical Specifications

ENGINE				
Model / Make	AVENGER 26 4WD			
HP Category	26			
Type	4 cycle, Vertical Overhead Valve, Cylinder in line, Swirl Chamber type			
No. of Cylinders	3			
Bore / Stroke (mm)	78 / 92			
Rated Engine (RPM)	2500			
Displacement (cc)	1318			
Fuel Pump	In-Line Type (ND-PFR M TYPE)			
Air Cleaner Type	Dry Type			
Cooling System	Water Cooled			
CLUTCH				
Type	Heavy Duty Dry Type Single Clutch			
Plate Size	Dia 224 mm			
TRANSMISSION				
Gear Box	6F + 2R Synchromesh			
ROAD SPEED KM/hr	FORWARD		REVERSE	
Gear	HIGH	LOW	HIGH	LOW
1	5.42	1.38	4.07	1.03
2	9.12	2.32		
3	14.67	3.73		
HYDRAULIC SYSTEM				
Type	2 Lever, ADDC			
Hydraulic Pump	Gear Type			
Linkage	TPL Category I			
Lifting Capacity (kg)	1000			
STEERING				
Type	Power Steering			
POWER TAKE OFF				
Type	R PTO, 3 Speeds		Live PTO (Optional)	
Splines	6			
PTO / Speed	543 / 914 / 1470 / R 407 @ 2500		540 @ 2100 (Optional)	

CAPACITIES (LITRES)	
Fuel Tank	25
Engine Sump	3.7
Cooling System	5.8
Transmission & Hydraulic	26
Steering System	1.3
ELECTRICAL INSTALLATION	
Battery	12V, 65Ah
Alternator	12V, 65A
Starter Motor	12V, 1.7 KW
MIN. TURNING RADIUS	
Without Brakes (m)	2.7
TYRE SIZE	
TURF Tyres 4WD	
Front	23 x 8.50 - 12
Rear	33 x 15.5 - 16.5
Weight (Kg.)	1230
FRONT DRIVE AXLE for 4WD Only	
Differential	
Total Ratio	1:11.27
Oil Capacity (Ltr.)	2.5±10%
BRAKES	
Type	Multi Disc Oil Immersed
DIMENSIONS	
TURF Tyres	
Overall Length	2860 mm
Width	1530 mm
Height	2335 mm
Ground Clearance	265 mm
Wheel Base	1590 mm
Front Track	970 mm
Rear Track	1120 mm

For further details please contact nearest dealer

## AVENGER TRACTORS

Patiala Road, Nabha-147 201 (Pb.) INDIA

E-mail : [info@avenger.co.in](mailto:info@avenger.co.in) | Website : [www.avenger.co.in](http://www.avenger.co.in)

Note : Being continuous development & improvement is our company policy, all products, and product specifications are subject to change without prior notice to improve Reliability, Function or Design or Otherwise.