

AVENGER 26 (with Industrial Tyres)

Technical Specifications

ENGINE						
Model / Make	MVS3L2	MVS3L2 / MHI				
HP Category	26					
Туре	4 cycle, Vertical Overhead Valve, Cylinder in line,					
	Swirl Chamber type					
No. of Cylinders	3					
Bore / Stroke (mm)	78 / 92					
Rated Engine (RPM)	2500					
Displacement (cc)	1319					
Fuel Pump	In-Line Type (ND-PFR M TYPE)					
Air Cleaner Type	Dry with Clogging Sensor					
Cooling System	Water Cooled					
CLUTCH						
Type	Heavy Duty Dry Type Single Clutch					
Plate Size	Dia 224 mm					
TRANSMISSION						
Gear Box	9F + 3R Constant Mesh					
ROAD SPEED KM/hr	F	FORWARD RI			EVERSE	
Gear	HIGH	MED	LOW	HIGH	MED	LOW
1	8.01	4.09	1.29	9.37	4.73	1.49
2	11.44	5.78	1.82			
3	18.82	9.5	2.99			
HYDRAULIC SYSTEM						
Туре	Open Center, ADDC					
Hydraulic Pump	Gear Type					
Hydraulic Pump Linkage	TPL Category IN					
Lifting Capacity (kg)	750					
STEERING						
Туре	Power Steering					
POWER TAKE OFF	OFF					
Туре	2 Speed					
Splines	6					
PTO / Speed	540 @ 2500 540 E @ 2035					

	roominoar opoomoationo			
CAPACITIES (LITRES)				
Fuel Tank	25			
Engine Sump	3.7			
Cooling System	5.8			
Transmission & Hydraulic	18±10%			
ELECTRICAL INSTALLATION				
Battery	12V, 65Ah			
Alternator	12V, 65A			
Starter Motor	12V, 1.7 KW			
MIN. TURNING RADIUS				
Without Brakes (m)	2.6			
TYRE SIZE	Industrial Tyre			
Front	23 x 8.5 - 12			
Rear	33 x 15.5 - 16.5			
Weight (Kg.)	1130			
FRONT DRIVE AXLE for 4WD Only				
Differential				
Total Ratio	1:13.81			
Oil Capacity (Ltr.)	3.2 Ltr.			
BRAKES				
Туре	Multi Disc Oil Immersed			
DIMENSIONS	Industrial Tyre			
Overall Length	2860			
Width	1495			
Height	2530			
Ground Clearance	280			
Wheel Base	1542			
Front Track	925			
Rear Track	1095			

For further details please contact nearest dealer

AVENGER TRACTORS

Patiala Road, Nabha-147 201 (Pb.) INDIA

E-mail: info@avenger.co.in | Website: www.avenger.co.in