



EUROPEAN SERIES

Definitely Built for
Hardcore Performance

AVENGER 60 XT 2WD



More Power in Less Fuel Consumption
Low Maintenance Cost

Available Tractor Range
20 HP to 100 HP



AVENGER 60 XT 2WD

Technical Specifications

ENGINE						
Model / Make	AVENGER 60 XT					
HP Category	60					
Type	Four Stroke DI					
No. of Cylinders	4 Cylinder, Vertical, Inline					
Bore / Stroke (mm)	105 / 118					
Rated Engine (RPM)	2200					
Displacement (cc)	4088					
Fuel Pump	Multicylinder Inline (BOSCH)					
Air Cleaner Type	Dry					
Cooling System	Water Cooled					
CLUTCH						
Type	Heavy Duty, Dry Type Double clutch					
Plate Size	(310 / 340) Cerametallic Friction					
TRANSMISSION						
Gear Box	8F + 2R, Combination of Sliding & Constant Mesh / 12+12					
ROAD SPEED KM/hr	FORWARD			REVERSE		
Gear	HIGH	LOW		HIGH	LOW	
1	11.21	2.84		15.77	3.99	
2	13.82	3.53				
3	22.89	5.82				
4	36.25	9.20				
HYDRAULIC SYSTEM						
Type	2 Lever, ADDC					
Hydraulic Pump	Gear Type					
Linkage	TPL Category I-II					
Lifting Capacity (kg)	1800 / 2200					
STEERING						
Type	Power Steering					

Note : As per our policy is that of continuous development, specifications may change without any prior notice.
For further details contact your nearest dealer.

E-mail : info@avenger.co.in
Website : www.avenger.co.in

POWER TAKE OFF	
Type	Dual Speed Live
Splines	6
PTO / Speed	540 and CR PTO
CAPACITIES (LITRES)	
Fuel Tank	67
Engine Sump	11
Cooling System	9.5
Transmission & Hydraulic	55 / 35 (12+12)
Steering System	2
ELECTRICAL INSTALLATION	
Battery	12V, 100Ah
Alternator	12V, 42A
Starter Motor	12V, 2.7 KW
MIN. TURNING RADIUS	
Without Brakes (m)	5.24
TYRE SIZE	
Front	7.50 - 16
Rear	16.9 x 28
Weight (Kg.)	2190 (W/O ROPS)
BRAKES	
Type	Multi Disc Oil Immersed
DIMENSIONS	
Overall Length	3875 mm
Width	1930 mm
Height upto Exhaust	2280 mm
Ground Clearance	415 mm
Wheel Base	2230 mm
Front / Rear Track	1425 mm / 1480 mm

Authorised Dealer :