



EUROPEAN SERIES

Definitely Built for
Hardcore Performance

AVENGER 60 XT 4WD



More Power in Less Fuel Consumption
Low Maintenance Cost

Available Tractor Range
20 HP to 100 HP



AVENGER 60 XT 4WD

Technical Specifications

ENGINE						
Model / Make	AVENGER 60 XT					
HP Category	60					
Type	Four Stroke DI					
No. of Cylinders	4 Cylinder, Vertical Inline					
Bore / Stroke (mm)	105 / 118					
Rated Engine (RPM)	2200					
Displacement (cc)	4088					
Fuel Pump	Multicylinder Inline (BOSCH)					
Air Cleaner Type	Dry					
Cooling System	Water Cooled					
CLUTCH						
Type	Heavy Duty DC / Double Clutch					
Plate Size	310 / 340					
TRANSMISSION						
Gear Box	12F + 12R Synchro Mesh					
ROAD SPEED KM/hr	FORWARD			REVERSE		
Gear	HIGH	MEDIUM	LOW	HIGH	MEDIUM	LOW
1	10.25	3.70	1.33	8.58	3.17	1.29
2	15.23	5.58	2.07	12.75	4.54	1.71
3	22.33	8.35	3.23	18.71	6.89	2.59
4	31.52	11.68	4.58	26.33	9.66	3.72
HYDRAULIC SYSTEM						
Type	2 Lever, ADDC					
Hydraulic Pump	Gear Type					
Linkage	TPL Category-II					
Lifting Capacity (kg)	2200					
STEERING						
Type	Power Steering					

Note : As per our policy is that of continuous development, specifications may change without any prior notice.
For further details contact your nearest dealer.

E-mail : info@avenger.co.in
Website : www.avenger.co.in

POWER TAKE OFF	
Type	Dual Speed Live / GPTO
Splines	6
PTO / Speed	540 and 1000
CAPACITIES (LITRES)	
Fuel Tank	67
Engine Sump	11
Cooling System	9.5
Transmission & Hydraulic	35
Steering System	2
ELECTRICAL INSTALLATION	
Battery	12V, 100Ah
Alternator	12V, 42A
Starter Motor	12V, 2.7 KW
MIN. TURNING RADIUS	
Without Brakes (m)	5.2
TYRE SIZE	
Front	9.5 - 24
Rear	16.9 - 28
Weight (Kg.)	2650
FRONT DRIVE AXLE	
Differential	Limited Slip
Bevel Ratio	1:2.133
Hub Ratio	1:6
Total Ratio	1:12.8
Diff. Oil Capacity (Ltr.)	5.5±10%
Hub Oil Capacity (Ltr.)	0.6±15% each side
BRAKES	
Type	Multi Disc Oil Immersed

Authorised Dealer :

