



EUROPEAN SERIES

Definitely Built for  
Hardcore Performance

AVENGER 65 XT 4WD



More Power in Less Fuel Consumption  
Low Maintenance Cost

Available Tractor Range  
20 HP to 100 HP



# AVENGER 65 XT 4WD

## Technical Specifications

ENGINE						
Model / Make	<b>AVENGER 65 XT</b>					
HP Category	65					
Type	Four Stroke DI					
No. of Cylinders	4 Cylinder, Vertical Inline					
Bore / Stroke (mm)	105 / 118					
Rated Engine (RPM)	2200					
Displacement (cc)	4088					
Fuel Pump	Multicylinder Inline (BOSCH)					
Air Cleaner Type	Dry					
Cooling System	Water Cooled					
CLUTCH						
Type	Heavy Duty DC / Double Clutch					
Plate Size	Cerametalic Friction Plate (310 / 340)					
TRANSMISSION						
Gear Box	12F + 12R Synchro Mesh					
ROAD SPEED KM/hr	FORWARD			REVERSE		
Gear	HIGH	MEDIUM	LOW	HIGH	MEDIUM	LOW
1	10.25	3.70	1.33	8.58	3.17	1.19
2	15.23	5.58	2.07	12.75	4.54	1.71
3	22.33	8.35	3.23	18.71	6.89	2.59
4	31.52	11.68	4.58	26.33	9.66	3.72
HYDRAULIC SYSTEM						
Type	2 Lever, ADDC					
<b>Hydraulic Pump</b>	Gear Type					
Linkage	TPL Category-II					
Lifting Capacity (kg)	2200					
STEERING						
Type	Power Steering					

Note : As per our policy is that of continuous development, specifications may change without any prior notice.  
For further details contact your nearest dealer.

**E-mail : [info@avenger.co.in](mailto:info@avenger.co.in)**  
**Website : [www.avenger.co.in](http://www.avenger.co.in)**

POWER TAKE OFF	
Type	Dual Speed Live / GPTO
Splines	6
PTO / Speed	540 and 1000
CAPACITIES (LITRES)	
Fuel Tank	67
Engine Sump	11
Cooling System	9.5
Transmission & Hydraulic	35
Steering System	2
ELECTRICAL INSTALLATION	
Battery	12V, 100Ah
Alternator	12V, 42A
Starter Motor	12V, 2.7 KW
MIN. TURNING RADIUS	
Without Brakes (m)	5.2
TYRE SIZE	
Front	9.5 - 24
Rear	16.9 - 28
Weight (Kg.)	2650
FRONT DRIVE AXLE	
Differential	Limited Slip
Bevel Ratio	1:2.133
Hub Ratio	1:6
Total Ratio	1:12.8
Diff. Oil Capacity (Ltr.)	5.5±10%
Hub Oil Capacity (Ltr.)	0.6±15% each side
BRAKES	
Type	Multi Disc Oil Immersed

Authorised Dealer :

