

## **AVENGER** 26 4WD (with Industrial Tyres)

## **Technical Specifications**

			•				
ENGINE							
Model / Make	S3L2-18.	S3L2-18.2/2500, MHI					
HP Category	26						
Туре	4 cycle, Vertical Overhead Valve, Cylinder in line,						
	Swirl Chamber type						
No. of Cylinders	3						
Bore / Stroke (mm)	78 / 92						
Rated Engine (RPM)	2500						
Displacement (cc)	1319						
Fuel Pump	In-Line Type (ND-PFR M TYPE)						
Air Cleaner Type	Dry with Clogging Sensor						
Cooling System	Water Cooled						
CLUTCH							
Type	Heavy Duty Dry Type Single Clutch						
Plate Size	Dia 224 mm						
TRANSMISSION							
Gear Box	9F + 3R Constant Mesh						
ROAD SPEED KM/hr	F	FORWARD REVERSE			E		
Gear	HIGH	MED	LOW	HIGH	MED	LOW	
1	8.1	4.09	1.29	9.37	4.73	1.49	
2	11.44	5.78	1.82				
3	18.82	9.5	2.99				
HYDRAULIC SYSTEM	Л						
Type	Open Center, ADDC						
Hydraulic Pump	Gear Type						
Linkage	TPL Category 1N						
Lifting Capacity (kg)	800						
STEERING							
Type	Power Steering						
POWER TAKE OFF							
Type	2 Speed						
Splines	6						
PTO / Speed	540 @ 2500						

	Toominous oppositions		
CAPACITIES (LITRES)			
Fuel Tank	25		
Engine Sump	3.7		
Cooling System	5.8		
Transmission & Hydraulic	18±10%		
ELECTRICAL INSTALLAT	TION		
Battery	12V, 65Ah		
Alternator	12V, 65A		
Starter Motor	12V, 1.7 KW		
MIN. TURNING RADIUS			
Without Brakes (m)	3.0		
TYRE SIZE	Industrial Tyre		
Front	23 x 8.5 - 12		
Rear	33 x 15.5 - 16.5		
Weight (Kg.)	1260		
FRONT DRIVE AXLE for	4WD Only		
Differential			
Total Ratio	1:13.81		
Oil Capacity (Ltr.)	3.2 Ltr.		
BRAKES			
Туре	Multi Disc Oil Immersed		
DIMENSIONS (in mm)	Industrial Tyre		
Overall Length	2860		
Width	1495		
Height	2530		
Ground Clearance	293		
Wheel Base	1542		
Front Track	925		
Rear Track	1095		
Steering wheel height	1380 (from ground)		

For further details please contact nearest dealer

## PREET TRACTORS PVT. LTD.

Patiala Road, NABHA-147 201 (Pb.) INDIA.

Email: info@avenger.co.in | Visit us at: www.avenger.co.in